

## Model 400 Welding Fume Extractor

Model # SS-400-WFE



The **Model 400 Portable Welding Fume Extractors** are simple and highly efficient source-capture fume extractors for welding fume control. Typical applications include *MIG welding fumes, TIG welding fumes, maintenance welding, stainless steel pipe welding, production welding, clean room welding, occasional stick welding, spot welding, brazing,* and more.

This source-capture welding fume extractor includes a flame-retardant, self-supportive flex arm for easy and varied placement. Other benefits include small footprint, portability handle, heavy-duty casters for easy maneuverability, quick change pre-filter, and a variable speed controller.

The **Model 400 Welding Fume Extractor** comes equipped with patented filtration media that is customized specifically for welding fume control. In most cases, **HEPA** filtration is utilized and offers up to 99.97% efficiency on particles 0.3 microns and larger. Other options include **ASHRAE** [up to 95% efficiency on particles 0.5 microns and larger] and **ULPA** filtration media [up to 99.9995% efficient on particles 0.12 microns and larger].

Portable Welding Fume Extractors are also available in a smaller model [SS-300-WFE] and two larger models [SS-450-WFE & SS-500-WFE-MP1].

### Product Features

- Variable speed controller (115V only)
- On/Off toggle switch (220V only)
- Portability handle
- Self-supportive, flexible arm
- 360-degree swivel arm
- Quiet, reliable, and low maintenance operation
- Low power consumption
- Long filter life
- Simple quick “no tool” filter change
- **Optional:** magnehelic gauge, hour counter



21221 FM 529 Rd, Cypress, TX 77433  
1.800.799.4609 • sales@sentryair.com

[www.sentryair.com](http://www.sentryair.com)

# Fume & Particulate Removal

## Product Specifications

MADE IN THE USA



SINCE 1983



6" Diameter,  
72" L Flex Arm

Dimensions are approximate  
Shown with optional accessories



21221 FM 529 Rd  
Cypress, TX 77433  
1.800.799.4609  
sales@sentryair.com

[www.sentryair.com](http://www.sentryair.com)

<b>Base Unit Dimensions</b>	<b>Length:</b> 22.5" (incl control box) <b>Width:</b> 20" <b>Height:</b> 19.5"
<b>Arm Dimensions</b>	6" Diameter, 72" L fire-retardant flex arm 10.5" diameter capture hood
<b>Cabinet Material</b>	16 Ga. carbon steel
<b>Weight (approximately)</b>	50 - 100 lbs.
<b>Air Volume (approximately)</b>	High – 700 CFM Low – 50 CFM
<b>Electrical</b>	115/1/60, 2.5 amps 220/1/50, 1.5 amps 8' grounded power cord with NEMA 5-15P plug
<b>Sound Level (at 3' from inlet)</b>	Approx. 60 dba (High)
<b>Main Filter Options</b>	<i>Depending on the Application:</i> <b>HEPA</b> [up to 99.97% efficiency on particles 0.3 microns and larger] <b>ASHRAE</b> [up to 95% efficiency on particles 0.5 microns and larger] <b>ULPA</b> [up to 99.9995% efficiency on particles 0.12 microns and larger]
<b>Limited Warranty (From Date of Shipment)</b>	Limited two year warranty on defects due to materials or workmanship.
<b>Patent #</b>	5,843,197